#### 1. PRODUCT IDENTIFICATION

Description BLUE GLAZE. It belongs to high temperature glazes. Compound of frit: CAS N°. 65997-18-4.

### Application

They can be applied by brush, spraying or dipping in single- and double-fired. For one firing it's advisable the addition of Monocol V. Temperature range 1240°C - 1340°C, recommended temperature 1260°C. It is advisable to test at extreme temperatures.

# 2. CHEMICAL COMPOSITION Metal oxides with concentrations less than 0.05% have not been determined

Li <sub>2</sub> O	1-5	ZnO	Cr <sub>2</sub> O <sub>3</sub>	CaF <sub>2</sub>		
Na <sub>2</sub> O	5-10	MnO	$B_2O_3$	Bi <sub>2</sub> O <sub>3</sub>	Co-Si	0-0.5
$K_2O$	5-10	CdO	$V_2O_5$	$P_2O_5$	HfO2	0-0.5
MgO	0-0.5	CoO	$MnO_2$	BeO	LOI	10-20
CaO	5-10	NiO	SiO <sub>2</sub> 40-80	CeO <sub>2</sub>	LOI	10-20
SrO		Al <sub>2</sub> O <sub>3</sub> 10-20	TiO <sub>2</sub> <b>0-0.5</b>	CuO		
BaO		Fe <sub>2</sub> O <sub>3</sub> <b>0-0.5</b>	ZrO <sub>2</sub> <b>5-10</b>	Pr <sub>2</sub> O <sub>3</sub>		
PbO		$Sb_2O_3$	$SnO_2$			

#### **3 PHYSICAL-CHEMICAL PROPERTIES**

Aspect	White powder		0,79
Color(fired)	Blue		355,55

## 4. COLORIMETRY \* By Minolta ChromaControl (S)

⊥ · 73 6	a. <b>0 9</b>	b <sup>.</sup> -11 8

5. DILATOMETRY	* Data obtained with dilatometer BÄHR mod DIL 801 L	10 <sup>-7</sup> C <sup>-1</sup>

(25-300)C°	(50-300)C°	(300-500)C°	(500-600)C°	T <sup>a</sup> Transformation	T <sup>a</sup> Softening	Melting point
105.2	107.8	132.7	229.3	503 C°	884 C°	>1000 C°

# 6. GRANULOMETRIC DISTRIBUTION (WET WAY) \* Data obtained by Malvern Instruments (Master Sizer 2000)

>10µ	>25µ	>40µ	>70µ	>120µ	D50µ
49.8	17.2	5.6	0.5	0.1	10.0

### 7. RECOMMENDATIONS ON GLAZED OBJECTS INTENDED FOR CULINARY USE

Formulated without lead and cadmium.

Notes: n.a (not applicable), n.d (no information available), p.n (negative tests)

