1. PRODUCT IDENTIFICATION

Description

GLOSSY TRANSPARENT RED GLAZE. It belongs to the "LIVE GLAZE" series. They have a colourful shiny finish and leave a high-quality surface finish. Compound of Frit CAS: 65997-18-4.

Application

Their Thermal Expansion Coefficient a=55-60 (300-500 °C) avoid cracking in commonly ceramic body. The transparent glazes in this series are designed for white clay bodies, but due to the density of some of the colours, these may be suitable for use on red clay bodies.

On red clay bodies, they can be single fired, and the addition of Monocol V (5%-10%) is recommended for better adhesion of the glaze to the piece.

They can be fired in traditional or fast firing cycles. The firing temperature varies from 960-1020°C

2. CHEMICAL COMPOSITION Metal oxides with concentrations less than 0.05% have not been determined.

Li ₂ O Na ₂ O	1-5	ZnO MnO	1-5	Cr ₂ O ₃ B ₂ O ₃	10-20	CaF ₂ Bi ₂ O ₃	Cd(S,Se) en ZrSiO4	5-10
K ₂ O	0-0.5	CdO		V_2O_5	.0 =0	P_2O_5	LOI	0.5-1
MgO	0-0.5	CoO		MnO_2		BeO		
CaO	1-5	NiO		SiO_2	40-80	CeO ₂		
SrO	0-0.5	Al_2O_3	5-10	TiO ₂	0-0.5	CuO		
BaO	1-5	Fe ₂ O ₃	0-0.5	ZrO_2		Pr ₂ O ₃		
PbO		Sb_2O_3		SnO_2				

3 PHYSICAL-CHEMICAL PROPERTIES

Aspect Pink powder

Color(fired) Red

4. COLORIMETRY * By Minolta ChromaControl (S)

L: 41.24 a: 44.86 b: 23.58

5. DILATOMETRY * Data obtained with dilatometer BÄHR mod. DIL 801 L

(25-300)C° (50-300)C° (300-500)C° (500-600)C° Ta Transformation Ta Softening Melting point 52.5 51.3 55.1 169.7 559 C° 641 C° >600 C°

6. GRANULOMETRIC DISTRIBUTION (WET WAY) * Data obtained by Malvern Instruments (Master Sizer 2000)

>10µ	>25µ	>40µ	>70µ	>120µ	D50µ
61.4	29.2	12.7	2.2	0	14.3

7. RECOMMENDATIONS ON GLAZED OBJECTS INTENDED FOR CULINARY USE

Contains inclusion cadmium pigment. To certify their food use, the final pieces must be submitted to lead migration test by an accredited laboratory.

Notes: n.a (not applicable), n.d (no information available), p.n (negative tests)

P. PRODESCO S.L