ESMALTE 5880 BLANCO MATE S/Pb. ATOM

1. PRODUCT IDENTIFICATION

Description

White Matt Glaze suitable for use on white and red rody, pottery and colored body. Compound of frit: CAS Nº. 65997-18-4.

Application

It can be applied :dipping, spraying, any mechanical method of application. It can be coloured with our Pigments "P" Series, keeping in mind it contains Zr and Zn. It is recommended to make previous test for colouring with natural oxides and firing cycles over 1080 °C. "CD Series" of On-glaze colours can be used for decoration. The recommended temperature varies from 980°C-1080°C.

2. CHEMICAL COMPOSITION Metal oxides with concentrations less than 0.05% have not been determined.

Li₂O Na₂O	5-10	ZnO 10-20 MnO	Cr ₂ O ₃ B ₂ O ₃ 5-10	CaF ₂ Bi ₂ O ₃	HfO2	0-0.5
K_2O	0-0.5	CdO	V ₂ O ₅	P_2O_5	MEDIUM	0-0.5
MgO CaO	0-0.5 5-10	CoO NiO	MnO ₂ SiO ₂ 40-80	BeO CeO₂	LOI	1-5
SrO		Al ₂ O ₃ 5-10	TiO ₂ 0-0.5	CuO		
BaO PbO	1-5	Fe ₂ O ₃ 0-0.5 Sb ₂ O ₃	ZrO ₂ 5-10 SnO ₂	Pr ₂ O ₃		

3 PHYSICAL-CHEMICAL PROPERTIES

White powder Aspect Color(fired) White matt

4. COLORIMETRY * By Minolta ChromaControl (S)

L: n.a a: **n.a** b: n.a

5. DILATOMETRY * Data obtained with dilatometer BÄHR mod. DIL 801 L

(25-300)C° (50-300)C° (300-500)C° (500-600)C° T^a Transformation T^a Softening Melting point 61.5 62.2 72.5 160 525 864 Cº >980 C°

6. GRANULOMETRIC DISTRIBUTION (WET WAY) * Data obtained by Malvern Instruments (Master Sizer 2000)

>10µ	>25µ	>40µ	>70µ	>120µ	D50µ
58.9	27.6	12.6	2.3	0	13.3

7. RECOMMENDATIONS ON GLAZED OBJECTS INTENDED FOR CULINARY USE

Formulated without lead and cadmium.

Notes: n.a (not applicable), n.d (no information available), p.n (negative tests)

