#### 1. PRODUCT IDENTIFICATION

Description

BRIGHT OPAQUE RED GLAZE. It belongs to the "EOSP" series, recommended for ceramicware. Compound of frit: CAS No. 65997-18-4.

Application

The glaze can be applied by dipping, brush, screen printing or spray and can be used for decoration of white body or red clay. The firing recommended temperature varies from 980 °C to 1150°C. They can be used at higher temperatures obtaining the same or even other finishes, wich will depend on the body.

# 2. CHEMICAL COMPOSITION Metal oxides with concentrations less than 0.05% have not been determined.

04 5-10
0-0.5
)

# **3 PHYSICAL-CHEMICAL PROPERTIES**

Aspect Red powder
Color(fired) Bright red

### 4. COLORIMETRY \* By Minolta ChromaControl (S)

L: **43.8** a: **43.2** b: **20.5** 

**5. DILATOMETRY** \* Data obtained with dilatometer BÄHR mod. DIL 801 L

(25-300)C°	(50-300)C°	(300-500)C°	(500-600)C°	T <sup>a</sup> Transformation	T <sup>a</sup> Softening	Melting point
59.95	59.43	63.04	99.04	592 C°	668 C°	>850 C°

>10µ	>25µ	>40µ	>70µ	>120µ	D50 <sub>k</sub>
60	30	13	2	0	15.5

#### 7. RECOMMENDATIONS ON GLAZED OBJECTS INTENDED FOR CULINARY USE

Contains inclusion cadmium pigment. To certify their food use, the final pieces must be submitted to lead migration test by an accredited laboratory.

Notes: n.a (not applicable), n.d (no information available), p.n (negative tests)

