Description

TRANSPARENT COPPER GREEN GLAZE. This is a very bright glaze recommended for ceramicware. Compound of frit: CAS N°. 65997-18-4.

Application

It can be applied: dipping, spraying, any mechanical application method. Glaze suitable for use on white, red and colored body. The firing recommended temperature varies from 980 °C to 1080°C. They can be used at higher temperatures obtaining the same or even other finishes, which will depend on the body.

## 2. CHEMICAL COMPOSITION Metal oxides with concentrations less than 0.05% have not been determined.

Li <sub>2</sub> O		ZnO <b>0-0.5</b>	Cr <sub>2</sub> O <sub>3</sub>	CaF <sub>2</sub>		
$Na_2O$	0-0.5	MnO	B <sub>2</sub> O <sub>3</sub> <b>5-10</b>	$Bi_2O_3$	MEDIUM	0-0.5
$K_2O$	1-5	CdO	$V_2O_5$	$P_2O_5$	LOI	1-5
MgO	0.5-1	CoO	$MnO_2$	BeO	Pig.Ing	0-0.5
CaO	0-0.5	NiO	SiO <sub>2</sub> 10-20	CeO <sub>2</sub>	Pig.ilig	0-0.5
SrO	1-5	Al <sub>2</sub> O <sub>3</sub> <b>5-10</b>	TiO <sub>2</sub> <b>0-0.5</b>	CuO <b>5-10</b>		
BaO	0-0.5	Fe <sub>2</sub> O <sub>3</sub> <b>0.5-1</b>	$ZrO_2$	Pr <sub>2</sub> O <sub>3</sub>		
PbO		$Sb_2O_3$	SnO <sub>2</sub>			

## **3 PHYSICAL-CHEMICAL PROPERTIES**

Aspect	Green powder	
Color(fired)	Copper green	

## 4. COLORIMETRY \* By Minolta ChromaControl (S)

1: 40.6	2: -6.5	b: -0.5

5. DILATOMETRY	* Data obtained with dilatometer BÄHR mod. DIL 801 L	10 <sup>-7</sup> C <sup>-1</sup>
O. DID (I OI I LIKI	Data obtained with dilatorneter DALIK Hod. Die ooi e	10 0

Melting point	T <sup>a</sup> Softening	T <sup>a</sup> Transformation	(500-600)C°	(300-500)C°	(50-300)C°	(25-300)C°
>850 Cº	706 Cº	582 Cº	112 76	74 66	70.86	71 03

6. GRANULOMETRIC DISTRIBUTION (WET WAY)					* Data obtained by Malvern Instruments (Master Sizer 2000
	0.5				

>10µ	>25µ	>40µ	>70µ	>120µ	D50µ
57.8	22.71	9.35	0.98	0	12.72

## 7. RECOMMENDATIONS ON GLAZED OBJECTS INTENDED FOR CULINARY USE

Formulated without lead and cadmium.

Notes: n.a (not applicable), n.d (no information available), p.n (negative tests)

