



**BATS ENGOBE PYROMULL**

---

Refractory Engobe for refractory protection up to 1550°C. Water based refractory paint of ceramic hardening. Ideal to rollers, batts, inferior tiles and spoons to avoid slag adhesion.

COMPOSITION: Aluminum Basis

Al<sub>2</sub>O<sub>3</sub> 81 %

SiO<sub>2</sub> 17 %

PHYSICAL PROPERTIES:

Classification temperature: 1550 °C ISO 1927-1

Bulk Density (Dry 110°C )2,90 Kg/dm<sup>3</sup> ISO 1927-6

Melting Temperature 1.700°C.

APPLICATION:

By Brush, Spatula or pulverization.

Approximated yield: 0,5 - 1 kg/m<sup>2</sup> (The yields may vary depending on the finish of the workpiece to be coated and the coats want to apply)

REMARKS

Packaging plastic box of 3,5 kg and 20 kg.

Keep firmly closed.

*No duden en contactar con nuestro Departamento Técnico para cualquier duda o aclaración.*

---

**Tienda**

Balmes, 29  
46940 Manises Valencia (ESPAÑA)

(+34) 96 154 88 21  
latienda@prodesco.es  
<http://prodesco.es>

**Fábrica**

Aviación, 44  
46940 Manises Valencia (ESPAÑA)

(+34) 96 154 55 88  
admon@prodesco.es  
<http://prodesco.es>